



ROLAIR STANDARD FEATURES

- PUMP:** ROLAIR Quality, Single Stage, Ball Bearings, Cast-Iron Cylinder, Stainless Steel Reed Valves and Splash Lubrication Ensure Longer Life.
Low RPM for Quiet Operation
- MOTOR:** 1.5 HP, 1700 RPM, Low Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

| MODEL | MOTOR HP | # OF CYLS. | CU.FT. DISPLACED | CU.FT. FREE AIR@100 PSI | TANK CAP. (GAL.) | DIMENSIONS (L X W X H) | APPROX. SHIPPING WEIGHT |
|-----------|----------|------------|------------------|-------------------------|------------------|------------------------|-------------------------|
| FC1250LS3 | 1.5 | 1 | 3.9 | 2.9 | 2.5 | 12" x 9" x 18" | 38 lbs. |

STANDARD EQUIPMENT

- Start/Stop Pressure Switch with On/Off Lever
- Air Line Regulator and Pressure Gauge
- Compact/Lightweight Tank Design
- Tank Pressure Gauge
- Safety Relief Valve
- Replaceable Filter Cartridge
- Initial 6 oz. Oil Fill Included
- Low Amp Motor



ROLAIR SYSTEMS

606 S. LAKE ST > P O BOX 346 > HUSTISFORD WI 53034-0346
SALES FAX: 920.349.3691 > SERVICE FAX: 920.349.8861
PHONE: 920-349-3281
www.rolair.com